

## SPECIFICATIONS

<b>FREQUENCY RESPONSE</b>	20 Hz to 40 KHz +/- 1 dB (at send output) 30 Hz to 30 KHz +/- 1 dB (at speaker output, with processor threshold exceeded)
<b>DISTORTION</b>	<0.05%, 20 Hz to 20KHz 1 dB below rated output
<b>SYSTEM SIGNAL TO NOISE RATIO</b>	>80 dB @ 1 w, "A" WTD
<b>POWER OUTPUT</b>	125W/ch continuous average power, 4 or 8 $\Omega$ , both channels driven with THD < 1%
<b>INPUT IMPEDANCE CHANNELS 1 - 4</b>	Mic Input: 2 k $\Omega$ Line Input: 66 k $\Omega$
<b>INPUT IMPEDANCE STEREO CHANNELS</b>	Phono: 78 k $\Omega$ 1/4": 78 k $\Omega$
<b>MAXIMUM INPUT LEVEL</b>	Mic Input: -7 dBu Line Input: 30 dBu Stereo Input: 26 dBu
<b>RETURN INPUT IMPEDANCE</b>	47k $\Omega$
<b>FUSE TYPE</b>	T6.3A, 250V
<b>RETURN SENSITIVITY</b>	0 dB for rated output power
<b>PASSPORT SYSTEM</b>	
Width	840 mm (33.7 in.)
Height	615 mm (24.2 in.)
Depth	300 mm (11.8 in.)
Weight	24 kgs (53 lbs)
<b>SPEAKERS</b>	
Width	340 mm (13.4 in.)
Height	610 mm (24.2 in.)
Depth	300 mm (11.8 in.)
Weight	6.8 kgs (15 lbs)
<b>POWER TOWER</b>	
Width	185 mm (7.3 in.)
Height	615 mm (24.2 in.)
Depth	300 mm (11.8 in.)
Weight	10.5 kgs (23 lbs)
Tower Footprint	350 x 300 mm (13.8 in. x 11.8 in.)
<b>MICROPHONES</b>	Dynamic Cardioid, balanced.
<b>CABLES</b>	XL -M to XL-F, 6 m. (20 feet)
<b>SPEAKER CABLES</b>	1/4 in. to 1/4 in., 9 m (30 feet)
	0 dBu is referenced to 0.775 volts rms